

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 November 2003 (06.11.2003)

PCT

(10) International Publication Number
WO 2003/090977 A1

(51) International Patent Classification⁷: **B25G 1/04**

SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,
YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/GB2003/001737

(22) International Filing Date: 23 April 2003 (23.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- with amended claims

Date of publication of the amended claims: 19 February 2004

(71) Applicant and

(72) Inventor: RIDGWAY, Michael [GB/GB]; 44 Richard Moss House, St. Peter Street, Winchester, Hampshire SO23 8BX (GB).

(74) Agent: ATCHLEY, Martin, J., W.; Chartered Patent Agent, 60A Christchurch Road, Winchester, Hampshire SO23 9SY (GB).

(48) Date of publication of this corrected version:

20 October 2005


(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,

(15) Information about Correction:

see PCT Gazette No. 42/2005 of 20 October 2005, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PAINTBRUSH ROTATION CONTROL SYSTEM



(57) Abstract: A system for rotating a paintbrush that connects handle (31), which may also be connected to an extension pole, to a paintbrush (10) comprises a rotary connection device (36) or silicone tube sections (80, 81) including a first member (56) having an internal cylindrical surface (57) and a second member (33) located within and substantially coaxial with the member (56) and having an external cylindrical surface. One member is attached to the handle (31), and the other to the paintbrush. The brush (10) is placed in a painting position against a surface with the axis of the brush extending substantially perpendicular to the surface and the handle (31) is moved with a circular motion substantially coinciding with the axis of the brush, the cylindrical surfaces of the two members will interact and cause the brush to rotate about its axis.